

DIRECT. ALIGNED. TO THE POINT.



Benchmark Example No. 13

Buckling of a Bar with Hinged Ends I

VERiFiCATION
BE13 Buckling of a Bar with Hinged Ends I

VERiFiCATION Manual, Service Pack 2024-4 Build 27

Copyright © 2024 by SOFiSTiK AG, Nuremberg, Germany.

SOFiSTiK AG

HQ Nuremberg
Flataustraße 14
90411 Nürnberg
Germany

T +49 (0)911 39901-0
F +49(0)911 397904

Office Garching
Parkring 2
85748 Garching bei München
Germany

T +49 (0)89 315878-0
F +49 (0)89 315878-23

info@sofistik.com
www.sofistik.com

This manual is protected by copyright laws. No part of it may be translated, copied or reproduced, in any form or by any means, without written permission from SOFiSTiK AG. SOFiSTiK reserves the right to modify or to release new editions of this manual.

The manual and the program have been thoroughly checked for errors. However, SOFiSTiK does not claim that either one is completely error free. Errors and omissions are corrected as soon as they are detected.

The user of the program is solely responsible for the applications. We strongly encourage the user to test the correctness of all calculations at least by random sampling.

Front Cover

6th Street Viaduct, Los Angeles Photo: Tobias Petschke

Overview

Element Type(s):	B3D
Analysis Type(s):	STAT, GNL
Procedure(s):	STAB
Topic(s):	
Module(s):	ASE
Input file(s):	buckling_bar.dat

1 Problem Description

The problem consists of an axially loaded long slender bar of length l with hinged ends, as shown in Fig. 1. Determine the critical buckling load. [1]




Figure 1: Problem Description

2 Reference Solution

The problem of lateral buckling of bars is examined here. The case of a bar with hinged ends is very often encountered in practical applications and is called the *fundamental* case of buckling of a prismatic bar. For the case of an axially compressed bar there is a certain critical value of the compressive force at which large lateral deflection may be produced by the slightest lateral load. For a prismatic bar with hinged ends (Fig. 1) this critical compressive force is [2]:

$$P_{cr} = \frac{\pi^2 EI}{(\beta l)^2} = \frac{\pi^2 EI}{l^2}, \quad (1)$$

where l is the full length of the bar, EI its flexural rigidity and β the effective length coefficient, whose value depends on the conditions of end support of the bar. For the fundamental case, $\beta = 1$. If the load P is less than its critical value the bar remains straight and undergoes only axial compression.

This straight form of elastic equilibrium is stable, i.e., if a lateral force is applied and a small deflection is produced this deflection disappears when the lateral load is removed and the bar becomes straight again. By increasing P up to the critical load causes the column to be in a state of unstable equilibrium, which means, that the introduction of the slightest lateral force will cause the column to undergo large lateral deflection and eventually fail by buckling.

3 Model and Results

Only the upper half of the bar is modelled because of symmetry (Fig. 1). The boundary conditions thus become free-fixed for the half symmetry model. A total of 20 elements are used to capture the buckling mode. The properties of the model are defined in Table 1.

Table 1: Model Properties

Material Properties	Geometric Properties	Loading
$E = 300 \text{ MPa}$	$l = 20 \text{ m}$	$P_y = 1 \text{ kN}$
	$h = 0.5 \text{ m}$	$P_x \ll 1 \text{ kN}$
	$A = 0.25 \text{ m}^2$	
	$I = 5.20833 \times 10^{-3} \text{ m}^4$	
	$\beta = 2$, free-fixed ends	




Figure 2: Load-Deflection curve

A small horizontal load at the top is necessary in order to induce an initial horizontal displacement. It should be sufficiently large to cause a nonlinear iteration, but it should not affect the result unintentionally. A buckling eigenvalue determination is performed where the critical load factor is calculated. The results are presented in Table 2. Moreover, an ultimate limit load iteration is done and the produced Load-Deflection curve is shown in Fig. 2, as well as a part of the iteration summary.

Table 2: Results

	SOF.	Ref.
P_{cr} [kN]	38.553	38.553

4 Conclusion

This example presents the buckling of slender bars. It has been shown that the buckling properties of the bar are accurately captured.

5 Literature

- [1] *Verification Manual for the Mechanical APLD Application, Release 12.0.* Ansys, Inc. 2009.
 - [2] S. Timoshenko. *Strength of Materials, Part II, Advanced Theory and Problems.* 2nd. D. Van Nostrand Co., Inc., 1940.
-